

ONE PUMP (#2000454)



PUMP ONE
ENVIRONMENTAL



APPLICATIONS

- Gas Extraction Wells
- Condensate Sumps
- Vertical Extraction Wells
- Recovery Wells at Remediation Sites

SPECIFICATIONS

- Product Number:** 2000454
- Pump Type:** Bottom Loading, High Temperature
- Actuation:** Float Activated, Fully Automatic
- Casing Material:** FRP
- Float:** Coated Syntactic
- Outer Diameter:** 3.5 in.
- Length:** 42.75 in.
- Weight:** 16.8 lbs.
- Volume/Stroke:** .32-.37 gal.
- Actuation Point:** 27.4 in. from bottom
- Max Flow Rate:** 12.5 GPM (See Flow Rate)
- Air Pressure:** 5-250 psi
- Operating Temperature:** up to 250°
- Air Consumption:** 0-5 SCFM
- pH Range:** 2-13
- Minimum Liquid Density:** .79
- Max Depth:** 425 ft.

MATERIALS

- Major Metallic Parts:** 316 SS, 17/4 SS & NdFeB
- Internal Non-Metallic parts:** PEEK, PTFE (Teflon), & FKM (Viton)

WARRANTY

The ONE Pump is built in the USA & protected by a 5-year warranty.



* Call PUMP ONE
for site specific
recommendations.

(704) 786-8158

sales@pumponellc.com
<https://pumponellc.com>

10308 Bailey Rd. Suite 418
Cornelius, NC 28031



ACCESSORIES



6 in. WELL SEAL
(#2000336)

8 in. WELL SEAL
(#2000335)

AIR REGULATOR KIT
(#200068)



FAST FITTING KIT
(#2000476)

AIR INTAKE MANIFOLD
(#200030)



LEACHATE DISCHARGE MANIFOLD
(#200032)

LEACHATE 2-WAY DISCHARGE MANIFOLD
(#2000153)



PUMP CURVES

