

ONE-V PUMP (# 2000469)



PUMP ONE
ENVIRONMENTAL



* Call PUMP ONE
for site specific
recommendations.

APPLICATIONS

Gas Extraction Wells
Condensate Sumps
Vertical Extraction Wells
Recovery Wells at Remediation Sites

SPECIFICATIONS

Product Number: 2000469
Pump Type: Bottom Loading, High Temperature, Viscous
Actuation: Float Activated, Fully Automatic
Casing Material: FRP
Float: Syntactic
Outer Diameter: 3.5 in.
Length: 42.75 in.
Weight: 16.0 lbs.
Volume/Stroke: .32-.37 gal.
Actuation Point: 27.4 in. from bottom
Max Flow Rate: 12.5 GPM (See Flow Rate)
Air Pressure: 5-250 psi
Operating Temperature: up to 250°
Air Consumption: 0-5 SCFM
pH Range: 2-13
Minimum Liquid Density: .79
Max Depth: 425 ft.

MATERIALS

Major Metallic Parts: 316 SS, 17/4 SS & NdFeB

Internal Non-Metallic parts: PEEK, PTFE (Teflon), & FKM (Viton)

WARRANTY

The ONE-V Pump is built in the USA & protected by a 5-year warranty.



(704) 786-8158



sales@pumponellc.com
<https://pumponellc.com>



10308 Bailey Rd. Suite 418
Cornelius, NC 28031

RELATED PARTS



6 in. WELL SEAL
(#2000336)

8 in. WELL SEAL
(#2000335)

AIR REGULATOR KIT
(#200068)



FAST FITTING KIT
(#2000476)

AIR INTAKE MANIFOLD
(#2000030)



LEACHATE DISCHARGE MANIFOLD
(#2000032)



LEACHATE 2-WAY DISCHARGE MANIFOLD
(#2000153)



PUMP CURVES

