


ONE-LDD PUMP (# 2000467)



APPLICATIONS

Gas Extraction Wells
Condensate Sumps
Vertical Extraction Wells
Recovery Wells at Remediation Sites

SPECIFICATIONS

Product Number: 2000467
Pump Type: Bottom Load, High Temp, Low Draw Down
Actuation: Float Activated, Fully Automatic
Casing Material: FRP
Float: Syntactic
Outer Diameter: 3.5 in.
Length: 27 in.
Weight: 12.2 lbs.
Volume/Stroke: .15 gal.
Actuation Point: 14.2 in. from bottom
Max Flow Rate: 5.3 GPM (See Flow Rate)
Air Pressure: 5-250 psi
Operating Temperature: up to 250°
Air Consumption: 0-5 SCFM
pH Range: 2-13
Minimum Liquid Density: .79
Max Depth: 425 ft.

MATERIALS

Major Metallic Parts: 316 SS, 17/4 SS & NdFeB
Internal Non-Metallic parts: PEEK, PTFE (Teflon), & FKM (Viton)

WARRANTY

The ONE-LDD Pump is built in the USA & protected by a 5-year warranty.

* Call PUMP ONE
for site specific
recommendations.



(704) 786-8158



sales@pumponellc.com
<https://pumponellc.com>



10308 Bailey Rd. Suite 418
Cornelius, NC 28031

ACCESSORIES



6 in. WELL SEAL
(#2000336)

8 in. WELL SEAL
(#2000335)

AIR REGULATOR KIT
(#200068)



FAST FITTING KIT
(#2000476)

AIR INTAKE MANIFOLD
(#200030)



LEACHATE DISCHARGE MANIFOLD
(#200032)

LEACHATE 2-WAY DISCHARGE MANIFOLD
(#2000153)



PUMP CURVES

